

15", Capacitive / Resistive Touch Screen, Industrial Touch Display



Features

- 15" LCD Capacitive / Resistive Touch
- Compact Structure, Front Panel IP65
- All Metal Structure Design, Durable
- Support Panel and VESA Installation



Specifications

Display		Power Specification	
Size	15-inch	Power Input	DC 12~24V
Resolution	1024 x 768	Power Adapter	AC-DC, 12V@5A, 60W
Viewing Angle	89/89/89/89	Power Consumption	13W(Typ.)
Color Support	16.7M	Environmental	
Brightness	350 cd/m ²	Operating Temperature	-10~50°C
Contrast Ratio	1000:1	Storage Temperature	-20~60°C
Response Time	3/0 (Typ.)(Tr/Td) ms	Relative Humidity	10%-90%, @ 40°C (non-condensing)
Backlight	LED	Vibration	5~500Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 Hour Per Axis
Backlight Life	50000h	Certifications	CE, FCC
Touch Screen		Mechanical	
Type	Projection Multi Touch Capacitive Touch Screen 5-wire Resistive Touch Screen	Housing	Aluminum Alloy Panel, All-metal Structure
Control Interface	USB	Mounting Method	Panel-mount, VESA-mount
Surface Hardness	≥6H & 3H	Dimension (W x L x H)	370x 294 x 41.5 mm
Transmittance	85% & 78%	Weight	3.41Kg
I/O Connectors		Packing List	
USB	1 x USB2.0		1 x DPM-1150
Display	1 x VGA 1 x DVI 1 x HDMI/DP		1 x AC-DC Power Adapter
Others	1 x DC-IN (2-Pin Phoenix)		1 x USB Control Cable
			1 x Cable Buckle
			1 x Certificate
			1 x Warranty Card
			8 X Panel Mounting Buckles

Dimensions

