

SPC-3191C



19" Stainless Steel Panel PC, Intel® Celeron® J1900 Processor, Medical-grade SUS 316



Features

- Intel® Celeron® J1900 (2.0 GHz)
- 19" industrial LCD panel and touch
- M12 I/O Connectors
- Medical-grade SUS 316 stainless steel housing
- Fanless and IP66 Protection
- -10~50°C operating temperature
- Optional 9~36VDC input
- Optional WiFi, Bluetooth, 4G, 5G



Specifications

System

| | |
|------------------|---|
| CPU | Intel® Quad-Core™ Celeron® J1900 (2.0GHz) |
| Memory | 1 x SO-DIMM DDR3L-1333/1600 (up to 8GB) |
| Storage | 1 x Full-size Mini-PCle for mSATA SSD |
| Operating System | Windows 7/10, Linux |

Display

| | |
|----------------|-----------------------|
| Size | 19-inch |
| Resolution | 1440 x 900 |
| Brightness | 250 cd/m ² |
| Contrast Ratio | 1000:1 |
| LED Lifetime | 30000 hrs |

Touch Screen

| | |
|------|-------------|
| Type | P-CAP touch |
|------|-------------|

I/O Connectors

| | |
|-------------|--------------------------------|
| Serial Port | 1 x RS-232, 1 x RS-232/485 |
| USB Port | 2 x USB2.0 |
| Ethernet | 2 x GbE LAN |
| Power | 1 x DC-in |
| Others | 1 x ATX Switch 2 x Speakers |

Expansion

| | |
|-----------|--|
| Mini-PCle | 1 x Full-size Mini-PCle for mSATA 1 x Full-size Mini-PCle |
|-----------|--|

Power Management

| | |
|-------------|-----------|
| Power Input | DC 12V |
| Consumption | 27W(Typ.) |

Environmental

| | |
|-----------------------|---------------------------------|
| Operating Temperature | -10~50°C |
| Storage Temperature | -20~60°C |
| Relative Humidity | 5%-90%, @ 40°C (non-condensing) |
| IP Protection | IP66 |

Mechanical

| | |
|-----------------------|-----------------|
| Material | SUS 316 |
| Mounting | VESA-mount |
| Dimension (W x L x H) | 495x 343 x 58mm |
| Weight | 8.3Kg |

Packing List

- 1 x SPC-3191C
- Power Adapter and Cord
- Interface conversion cord
- 1 x Certificate
- 1 x Warranty Card

Dimensions

